

PaintersChoice

Material Safety Data Sheet

PRODUCT IDENTITY: PC-30 High Build lacquer Primer Grey

Section I – Manufacturer Information

Manufacturer Name: Performance Products

Address: PO Box 463
Lansing IL 60438

Telephone for information: 866-228-6528

Emergency Telephone: Chemtrec 800-262-8200

NFPA Ratings

Health	2
Flammability	3
Reactivity	0
Personal	
Protection	G

Section II-Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name)

	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Wt %</u>
*TOLUENE	108-88-3	100 ppm	100 ppm	5/10
*XYLENE	1330-20-7	100 ppm	100 ppm	1/5
2-PROPANOL	67-63-0	400 ppm	400 ppm	1/5
ACETONE	67-64-1	750 ppm	750 ppm	25/35
METHYL ISOBUTYL KETONE	108-10-1	100 ppm	50 ppm	5/10

* SARA 313 listed chemical

DOT SHIPPING: FLAMMABLE LIQUID; PAINT RELATED MATERIAL

Section III-Physical/Chemical Characteristics

Boiling Point: 132° F

Specific Gravity (H₂O = 1): 1.08

Vapor Pressure (mmHg @ 70°F): 185 mmHg

Vapor Density (Air = 1): Heavier than Air

Evaporation Rate: (butyl acetate = 1) >1

Coatings V.O.C. 2.74 lbs. /gal, 329.1 gm. /l

Appearance and Odor: Gray colored viscous Liquid, Ketone Solvent Odor

Material V.O.C. 2.1 lbs. /gal, 254.4 gm. /l

Section IV-Fire and Explosion Hazard Data

Flash Point (Method Used): < 20°F (TCC)

Flammable Limits: LEL 1.0 UEL 12.8

Extinguishing Media

Class B extinguisher, Carbon Dioxide, Dry Chemical, Foam Special Fire Fighting Procedures

Water spray can be used to cool containers exposed to fire. Clear area of unprotected personnel. Fire fighters are to wear self-contained breathing apparatus and proper protection gear. Keep containers closed tightly. Isolate from heat, sparks, and open flames.

Unusual Fire and Explosion Hazards

Closed containers may explode when exposed to extreme heat.

Section V- Reactivity Data

Stability – Unstable: Conditions to Avoid: Sources of ignition

Stable: Yes

Incompatibility (Materials to Avoid): Strong Oxidizers

Hazardous Decomposition products: Carbon monoxide, Carbon dioxide, and Oxides of nitrogen

Hazardous Polymerization: Will not occur

Section VI- Health Hazard Data

Routes of Entry: Inhalation? Yes Skin? Yes Ingestion? Yes

Health Hazards (Acute and Chronic)

May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long-term exposure (years) vapor may cause lung, liver or kidney damage. The solvents listed have been reported to affect the central nervous system. Signs and Symptoms of Exposure: Inhalation - difficulty in breathing; Skin – redness; Ingestion - vomiting
Medical Conditions Generally Aggravated by Exposure: Heart Disease; respiratory disorders.

Emergency and First Aid Procedures:

If overcome by vapors give oxygen. Do not induce vomiting. Wash eyes with large quantities of water.
Wash skin with soap and water.

Carcinogenicity NTP? No IARC Monographs? No OSHA? No

Section VII - Precautions for Safe handling and Use

Steps to be taken in Case Material is Released or Spilled- -Eliminate all sources. Scrape up with NONSPARKING tools. Remove outside area away from ignition sources. FLASHBACK POSSIBLE.

Waste Disposal Method--

Dispose as hazardous waste in accordance with EPA RCRA.

Precautions to be taken in Handling and Storing- Keep away from heat, sparks or open flame. Store at temperatures below 120F

Other Precautions - -

Excessive skin contact may defat skin causing dermatitis.

Respiratory Protection (Specify Type):

Self contained breathing apparatus if above TLV limit exceeding.

Ventilation Local Exhaust:

YES Mechanical (General)

Protective Gloves: Neoprene, Viton

Eye Protection: Wear eye protection.

Other Protective Clothing or Equipment: N/A

Work/Hygienic Practices: Do not smoke while using. Wash your hands after every use. Avoid unnecessary exposure and removal of the material from skin and clothing.

* SARA

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Super Fund Amendments and Reauthorization Act (SARA) of 1996 and 40 CFR Part 372. You must notify each person to whom this mixture or trade name product is sold. This statement must remain a part of this Material Data Safety Sheet. This statement must not be detached. Any copy or redistribution of this Material Data Safety Sheet shall include this statement.